

METAL BELLOW SEAL

# TARSEAL NT8

DIN 24960

## MATERIAL ALTERNATIVES

Sliding faces	O-rings	Other parts
SiC/SiC Carbon/SiC	FPM, EPDM, NBR Perfluoroelastomer	Hastelloy C Inconel 625

METAL BELLOW SEAL

**TARSEAL NT8**  
DIN 24960

d1 h7	d2	d3	d4	d6	d7 H8	d8	l1 ± 0,5	l3
24	38.1	38.4	44.0	33	39	3	30.0	12.7
25	39.0	38.4	44.0	34	40	3	30.0	12.7
28	42.0	41.6	47.2	37	43	3	32.5	12.7
30	44.0	47.9	53.6	39	45	3	32.5	12.7
32	46.0	47.9	53.6	42	48	3	32.5	12.7
33	47.0	51.1	56.7	42	48	3	32.5	12.7
35	49.2	51.1	56.7	44	50	3	32.5	12.7
38	52.4	54.3	59.9	49	56	4	34.0	12.7
40	55.6	57.4	63.1	51	58	4	34.0	12.7
43	58.7	60.6	66.3	54	61	4	34.0	12.7
45	58.7	63.8	69.4	56	63	4	34.0	12.7
48	61.9	67.0	72.6	59	66	4	34.0	12.7
50	65.1	67.0	72.6	62	70	4	34.5	12.7
53	68.3	70.1	75.8	65	73	4	34.5	14.3
55	71.0	73.3	78.8	67	75	4	34.5	14.3
60	74.6	76.5	82.1	72	80	4	39.5	14.3
63	81.0	82.8	88.5	75	83	4	39.5	15.9
65	84.1	86.0	91.7	77	85	4	39.5	15.9
70	87.3	89.2	94.8	83	92	4	45.0	15.9
75	95.3	95.5	101.2	88	97	4	45.0	15.9
80	98.4	98.7	104.4	95	105	4	44.5	15.9
85	104.8	105.0	110.7	100	110	4	44.5	15.9
90	108.0	108.2	113.9	105	115	4	49.5	17.5
95	114.3	114.6	120.2	110	120	4	49.5	17.5
100	120.7	120.9	126.6	115	125	4	49.5	17.5