

TARSEAL TA502

DIN 24960

MATERIAL ALTERNATIVES

Sliding faces	O-rings/Rubber parts	Other parts
SiC/SiC Carbon/SiC	FPM, EPDM, NBR	AISI 316

TARSEAL TA502

DIN 24960

DIMENSIONS

Type	d1 h7	d2	d7 h8	l1	l2
TA502/14	14	24	25	35	23,3
TA502/16	16	26	27	35	23,3
TA502/18	18	32	33	37,5	24,3
TA502/20	20	34	35	37,5	24,3
TA502/22	22	36	37	37,5	24,3
TA502/24	24	38	39	40.0	27
TA502/25	25	39	40	40.0	27,3
TA502/28	28	42	43	42.5	30.3
TA502/30	30	44	45	42.5	30.8
TA502/32	32	46	48	42.5	30.8
TA502/33	33	47	48	42.5	30.8
TA502/35	35	49	50	42.5	30.8
TA502/38	38	54	56	45.0	32.3
TA502/40	40	56	58	45.0	32.3
TA502/43	43	59	61	45.0	32.3
TA502/45	45	61	63	45.0	32.3
TA502/48	48	64	66	45.0	32.3
TA502/50	50	66	70	47.5	34.3
TA502/53	53	69	73	47.5	34.3
TA502/55	55	71	75	47.5	34.3
TA502/58	58	78	78	52.5	39.3
TA502/60	60	80	80	52.5	39.3
TA502/63	63	83	83	52.5	39.3
TA502/65	65	85	85	52.5	39.3
TA502/68	68	88	90	52.5	39.3
TA502/70	70	89	92	60.0	45.3
TA502/75	75	96	97	60.0	45.3
TA502/80	80	104	105	60.0	45.3
TA502/85	85	108	110	60.0	45.3
TA502/90	90	114	115	65.0	50.3
TA502/95	95	118	120	65.0	50.3
TA502/100	100	124	125	65.0	50.3